

MJ9320

平台扫码器

Platform Barcode Reader

物理特性/Physical Characteristics

尺寸 Dimensions : 96.7mm x 104mm x 145mm

电压 Voltage : 5V

待机电流 Stand-by Current : 193mA

重量 Weight : 297.5g

开机电流 Starting Current : 360mA

工作电流 Work Current : 335mA

性能指标/Performance Characteristics

传感器像素 Image (Pixels) : CMOS 640 pixels (H) x 480 pixels (V)

光源 Light Source : Red color LED

视场角 Field of View : 39°(H) X29°(V)

旋转倾斜偏转 Roll / Pitch / Yaw : 360°, ±65°, ±65°

打印对比度 Print Contrast : 20% minimum reflective difference

接口支持 Interfaces Supported : USB

识读精度 Resolution : ≥3mil

解码能力/Symbology Decode Capability

一维条码/1-D: Codabar、Code 39、Code 32 Pharmaceutical (PARAF)、Interleaved 2 of 5、NEC 2 of 5、Code 93、Straight 2 of 5 Industrial、Straight 2 of 5 IATA , Matrix 2 of 5 , Code 11、Code 128、GS1-128、UPC-A、UPC-E、EAN/JAN-8、EAN/JAN-13、MSI、GS1 DataBar Omnidirectional、GS1 DataBar Limited、GS1 DataBar Expanded、China Post(Hong Kong 2 of 5)、Korea Post.

二维条码/2-D: DOT Code, Codeblock A、Codeblock F、PDF417、Micro PDF417、GS1 Composite Codes、QR Code、Data Matrix、MaxiCode、Aztec、HANXIN.

默认开启码制: Codabar、Code39、Interleaved2of5、NEC2of5、Code93、Code128、GS1-128、UPC-A、UPC-E0、EAN/JAN-13、EAN/JAN-8、GS1-DataBar、PDF417、QR、DM、Aztec

用户环境参数/User Environment

工作温度 Operating Temperature : -20°C to 60°C

存储温度 Storage Temperature : -30°C to 70°C

湿度 Humidity : 5% to 95% relative humidity, non-condensing

抗震性 Shock Specifications : Designed to withstand 1.2m(5') drops

环境光免疫 Ambient Light Immunity : 0-100,000 Lux.

解码范围/Decode Ranges

Code39(5mil) : 0-9cm

Code39(13mil) : 0-17.5cm

UPC-A(13mil) : 1-17cm

支付宝支付码(QR 3*3) : 1-32cm

Performance may be impacted by bar code quality and environmental conditions



外观尺寸 (单位: 毫米) / Dimension (unit: mm)

